

Transportkettingen met hollebout

DIN 8165 met rol DIN 8166*

Köbo Nr.	p mm	b ₁ mm min.	b ₂ mm max.	d ₁ mm	d ₂ mm 0	d ₃ mm A	d ₄ mm B	d ₅ mm D	holle- out gat d ₆ mm min.	F ₂ mm	F ₃ mm	h mm	s mm	f cm ²	F _{Bh} N min.
405	63 80 100 125 160	22	31	12	18	26	40	- 50/60*	8	44,0	54,0	30	4	3,72	46000
406	63 100 125 160 200 250	25	36	14	20	30	48	- 63/73*	10	51,2	61,0	35	5	5,04	73000
407	100 125 160 200 250	30	43	16	22	32	55	72/87	11	60,2	70,0	40	6	6,88	90000
408	100 125 160 200 250	35	48	18	26	36	60	- 80/95	12	65,3	79,0	45	6	6,88	90000
409	125 160 200 250 315	45	63	20	30	42	70	- 100/120	14	84,8	99,0	50	8	12,60	145000
411	125 160 200 250 315	55	73	26	36	50	80	- 125/145	18	95,3	113	60	8	18,98	215000
412	160 200 250 315 400	65	87	30	42	60	90	- 140/170	20	113,3	130	70	10	26,10	295000
414	160 200 250 315 400	70	96	32	44	60	100	- 140/170	20	113,3	130	70	10	26,10	295000
416	160 200 250 315 400	80	106	36	50	70	110	- - 160/195	26	138,3	160	80	12	38,16	440000

* = staal

Andere hollebout transportkettingen: DIN 8168 blz. 154; fabrieksnorm blz. 163; ZC serie blz. 166
Voor kettinggewicht DIN 8165 zie blz. 138

