

# Transportkettingen

Uitgevoerd als draagketting - DIN 8165 FVT

Köbo Nr.	Din Nr.	p mm	b <sub>1</sub> mm min.	b <sub>2</sub> mm max.	d <sub>1</sub> mm max holle-bout	d <sub>2</sub> mm max	d <sub>4</sub> mm	d <sub>6</sub> mm min.	F <sub>1</sub> mm	F <sub>2</sub> mm	F <sub>3</sub> mm	h <sub>1</sub> mm	s mm	h <sub>2</sub> mm	F cm <sup>2</sup>	F <sub>B</sub> N min.	F <sub>Bh</sub> N min.
T203	FVT 40	40 50 63 80 100	18	25	10	15	32	-	36,0	-	43,0	35	3	22,0	2,50	42000	-
T205	FVT 63	63 80 100 125 160	22	31	12	18	40	8	440	44,0	54,0	40	4	25,0	3,72	64000	46000
T206	FVT 90	63 100 125 160 200 250	25	36	14	20	48	10	52,0	51,2	61,0	45	5	27,5	5,04	100000	73000
T207	FVT 112	100 125 160 200 205	30	43	16	22	55	11	61,0	60,2	70,0	50	6	30,0	6,88	120000	90000
T208	FVT 140	100 125 160 200 250	35	48	18	26	60	12	66,0	65,3	79,0	60	6	37,5	8,64	145000	110000
T209	FVT 180	125 160 200 250 315	45	63	20	30	70	14	85,5	84,8	99,0	70	8	45,0	12,60	190000	145000
T211	FVT 250	125 160 200 250 315	55	73	26	36	80	18	97,5	95,3	113	80	8	50,0	18,98	275000	215000
T212	FVT 315	160 200 250 315 400	65	87	30	42	90	20	117	113,3	130	90	10	55	26,10	370000	295000
T214	FVT 400	160 200 250 315 400	70	96	32	44	100	22	130	127,3	148	90	12.	55	30,72	410000	330000
T216	FVT 500	160 200 250 315 400	80	106	36	50	110	26	140	138,3	160	100	12	60	38,16	540000	440000

Andere transportkettingen als draagketting: DIN 8167 blz. 148 + 149; DIN 8168 blz. 157  
Voor kettinggewicht DIN 8165 zie blz. 138