

Transportketting

Afmetingen standaard bevestigingslippen - DIN 8165 FV

Köbo Nr.	Din Nr.	p mm	a ₁ mm min.	a ₂ * mm max.	B mm max	d mm max	H* mm	W ₁ mm max	hoekijzer	gewicht kg / st.
203	FV 40	40	-	-	-	-	-	-	-	-
		50	•	25	25	6,4	20	49	■	0,02
		63	•		31				■	0,03
		80	•		40				■	0,04
		100	30		50				■	0,05
205	FV 63	63	•	34	40	8,4	30	50	■	0,05
		80	•		40				30x 30x 4	0,07
		100	30		50					0,09
		125	40		60					0,12
		160	50		70					0,14
206	FV 90	63	-	-	-	-	-	-	-	-
		100	30	40	50	8,4	35	63	40x 40x 5	0,15
		125	40		60					0,19
		160	50		70					0,24
		200	60		80					0,27
250	65		85					0,30		
207	FV 112	100	30	50	50	11	40	68	40x 40x 6	0,18
		125	40		65					0,23
		160	50		75					0,28
		200	65		90					0,35
		250	80		105					0,47
208	FV 140	100	30	50	55	11	45	80	50x 50x 7	0,28
		125	40		65					0,33
		160	50		75					0,41
		200	65		90					0,51
		250	80		105					0,69
209	FV 180	125	35	64	63	13	45	90	50x 50x7	0,33
		160	50		80					0,41
		200	65		95					0,51
		250	80		110					0,69
		315	100		130					0,82
211	FV 250	125	•	69	50	12	55	110	65x 65x 7	0,39
		160	50		80					0,62
		200	65		95					0,77
		250	80		110					1,04
		315	100		130					1,23
212	FV 315	160	•	85	50	13	60	124	70x 70x 11	0,65
		200	65		95					0,93
		250	80		110					1,25
		315	100		130					1,48
		400	100		130					1,48
214	FV 400	160	•	95	50	17	65	131	70x 70x 11	0,78
		200	60		100					1,12
		250	80		120					1,50
		315	100		140					1,78
		400	100		140					1,78
216	FV 500	160	•	100	50	17	70	146	80x 80x 1	0,84
		200	50		90					1,25
		250	80		120					1,88
		315	100		140					2,23
		400	100		140					2,23
218	FV 630	200	•	115	50	17	80	171	100x 100x 12	1,24
		250	70		110					2,13
		315	100		140					2,83
		400	100		140					2,83
		500	100		140					2,83

• = 1 bev. gat

* niet aan toleranties gebonden

■ = aangebogen lip

Andere transportkettingen met bevestigingslippen: DIN 8167 blz. 152 + 153; DIN 8168 blz. 155

Voor kettinggewicht DIN 8165 zie blz. 138

