

Schrapertransportketting

DIN 8165

Köbo Nr.	p mm	b ₁ mm min.	b ₂ mm max.	d ₁ mm	d ₂ mm	F ₁ mm	F ₃ mm	h mm	s mm	f cm ²	f _B N min.	Type A+B	Type K		
												B ₁ mm	h _k mm	B _k * mm min.	B _k mm max.
303	63 80 100	18	25	10	15	36,0	43,0	26	3	2,50	42000	Door u op te geven totale schrapperbreedte bij aanvraag of bestelling	-	-	-
305	63 80 100 125 160	22	31	12	18	44,0	54,0	30	4	3,72	64000		-	-	-
306	63 100 125 160 200 250	25	36	14	20	52,0	61,0	35	5	5,04	100000		42	135 195 250 300	185 245 295 330
307	100 125 160 200 250	30	43	16	22	61,0	70,0	40	6	6,88	120000		42	145 200 260 310	195 255 305 340
308	100 125 160 200 250	35	48	18	26	66,0	79,0	45	6	8,64	145000		47	185 240 290 340	235 285 335 385
309	125 160 200 250 315	45	63	20	30	85,5	99,0	50	8	12,60	190000		52	195 250 310 360	245 305 355 405
311	125 160 200 250 315	55	73	26	36	97,5	113	60	8	19,98	275000		62	410 320	500 400
312	160 200 250 315 400	65	87	30	42	117	130	70	10	26,10	370000		-	-	-
314	160 200 250 315 400	70	96	32	44	130	148	70	12	30,72	410000		-	-	-
316	160 200 250 315 400	80	106	36	50	140	160	80	12	38,16	540000		-	-	-
318	200 250 315 400 500	90	116	42	56	152	169	100	12	48,72	630000		-	-	-

* B_k = STANDAARD, KAN OP VERZOEK INGEKORT WORDEN.

Voor kettinggewicht DIN 8165 zie blz. 138

