

Schrapertransportketting

DIN 8167 M-serie

ISO Nr.	p mm	b ₁ mm min.	b ₂ mm max.	d ₁ mm	d ₂ mm	F ₁ mm	F ₃ mm	h mm	s mm	f cm ²	f _B N	Type A+B	Type K		
												B ₁ mm	h _k	B _k min.	B _k max.
M 56	100 125 160 200 250	24	33	10	15	47,2	56,2	30	4	3,30	56000	Door u op te geven totale schraperbreedte bij aanvraag of bestelling	-	-	-
M 80	100 125 160 200	28	39	12	18	55,2	64,2	35	5	4,68	80000		42	140 195 250 305	190 245 300 335
M 112	128 160 200	32	45	15	21	64,2	75,2	40	6	6,75	112000		42	145 200 260 310	195 255 305 340
M 160	125 160 200	37	52	18	25	73,3	88,3	50	7	9,36	160000		52	180 240 295 345	235 290 340 395
M 224	125 160 200 250	43	60	21	30	86,3	99,3	60	8	12,60	224000		62	400 310	490 390
M 315	160 200 250 315	48	90	25	36	100,3	120,3	70	10	17,5	315000		-	-	-
M 450	200 250 315 400	56	82	30	42	117,3	141,3	80	12	24,60	450000		-	-	-

Voor kettinggewicht DIN 8167 zie blz. 152 + 153

