

Transportketting met massieve bout

DIN 8167 (ISO 1977) M-serie

ISO Nr.	PΔ mm	b ₁ mm min.	b ₂ mm max.	d ₁ mm	d ₂ mm 0	d ₃ mm A	d ₄ mm B	d ₅ mm D	f ₁ mm	f ₃ mm	h mm	s mm	f cm ²	F _B N min.
M 160	100 125 160 200 250 315 400 500	37	52	18	25	36	70	70/85	73,3	88,3	50	7	9,36	160000
M 224	125 160 200 250 315 400 500 600	43	60	21	30	42	85	85/100	86,3	99,3	60	8	12,60	224000
M 315	160 200 250 315 400 500 630	48	70	25	36	50	100	100/200	100,3	120,3	70	10	17,50	315000
M 450	200 250 315 400 500 630 800	56	82	30	42	60	120	120/140	117,3	141,3	80	12	24,60	450000
M 630	250 315 400 500 630 800 1000	66	96	36	50	70	140	140/170	136,6	159,3	100	14	34,56	630000
M 900	250 315 400 500 630 800 1000	78	112	44	60	85	170	170/210	157,3	179,3	120	16	49,28	900000

Δ Voorkeurssteek (i.v.m. voorradige kettingwielen) elke andere steek is leverbaar op verzoek

Rollenmateriaal: Staal, gehard

Andere massieve bout transportkettingen: DIN 8165 blz. 131; Z serie blz. 164
Voor kettinggewicht DIN 8167 zie blz. 138

