

# Transportketting met hollebout

DIN 8168 MC-serie

ISO Nr.	p mm	b <sub>1</sub> mm min.	b <sub>2</sub> mm max.	d <sub>1</sub> mm	d <sub>2</sub> mm 0	d <sub>3</sub> mm A	d <sub>4</sub> mm B	d <sub>5</sub> mm D	d <sub>6</sub> mm min.	F <sub>2</sub> mm	F <sub>3</sub> mm	h mm	s mm	f cm <sup>2</sup>	F <sub>Bh</sub> N min.
MC 28	63 80 100 125 160	20	28	13	17,5	25	36	36/42	8,2	40,6	47,2	25	3,5	3,64	28000
MC 56	80 100 125 160 200 250	24	33	15,5	21	30	50	50/60	10,2	46,6	56,2	35	4	5,11	56000
MC112	100 125 160 200 250 315	32	45	22	29	42	70	70/85*	14,3	63,8	75,2	50	6	9,9	112000
MC224	160 200 250 315 400 500	43	60	31	41	60	100	100/120*	20,3	82,9	99,3	70	8	18,6	224000

Rollenmateriaal: Staal, gehard

Andere hollebout transportkettingen: DIN 8165 blz. 133; fabrieksnorm blz. 163; ZC serie blz. 166  
Voor kettinggewicht DIN 8168 zie blz. 157

