



Materiaal: Ck45 DIN 1.1191  
 Drukhoek: 20°  
 Vertandingskwaliteit: 8e25 DIN 3962/63/67

Art.nummer	z	D <sub>o</sub>	D <sub>a</sub>	D <sub>n</sub>	L <sub>n</sub>	B <sub>H7</sub>	Z <sub>e</sub>
4C300120	12	36	42	25	50	15	30
4C300130	13	39	45	30	50	15	30
4C300140	14	42	48	30	50	15	30
4C300150	15	45	51	35	50	15	30
4C300160	16	48	54	35	50	15	30
4C300170	17	51	57	40	50	15	30
4C300180	18	54	60	45	50	15	30
4C300190	19	57	63	45	50	15	30
4C300200	20	60	66	45	50	15	30
4C300210	21	63	69	50	50	15	30
4C300220	22	66	72	50	50	15	30
4C300230	23	69	75	55	50	15	30
4C300240	24	72	78	55	50	15	30
4C300250	25	75	81	60	50	15	30
4C300260	26	78	84	65	50	15	30
4C300270	27	81	87	65	50	15	30
4C300280	28	84	90	70	50	15	30
4C300290	29	87	93	70	50	15	30
4C300300	30	90	96	75	50	20	30
4C300310	31	93	99	80	50	20	30
4C300320	32	96	102	80	50	20	30
4C300330	33	99	105	80	50	20	30
4C300340	34	102	108	85	50	20	30
4C300350	35	105	111	85	50	20	30
4C300360	36	108	114	90	50	20	30
4C300370	37	111	117	90	50	20	30
4C300380	38	114	120	95	50	20	30
4C300390	39	117	123	100	50	20	30
4C300400	40	120	126	100	50	20	30
4C300420	42	126	132	100	50	20	30
4C300450	45	135	141	100	50	20	30
4C300480	48	144	150	100	50	20	30
4C300500	50	150	156	110	50	25	30
4C300540	54	162	168	110	50	25	30
4C300560	56	168	174	120	50	25	30
4C300600	60	180	186	120	50	25	30
4C300720	72	216	222	120	50	25	30
4C300800	80	240	246	120	50	30	30