

Profiel SPC/22											
Steekcirkel d_d (mm)	Aantal groeven	Uitvoering		Gewicht zonder klembus (≈ kg)	Klembus- Nr.	Steekcirkel d_d (mm)	Aantal groeven	Uitvoering		Gewicht zonder klembus (≈ kg)	Klembus- Nr.
200 [▲]	3	I	4	9,0	2517	355	3	O	5	22,9	3535
	4	I	4	10,5	3020		4	O	9	28,3	3535
	5	I	4	14,0	3535		5	O	9	32,5	3535
	6	I	4	17,0	3535		6	O	9	36,0	3535
212 [▲]	3	I	4	10,0	3020	375	8	O	9	67,5	4040
	4	I	4	12,5	3020		10*	O	9	121,0	4545
	5	I	4	15,0	3535		3	O	5	23,8	3535
	6	I	4	18,0	3535		4	O	9	30,0	3535
224	2	I	4	8,1	3020	400	5	O	9	33,0	3535
	3	I	4	11,0	3020		6	O	9	45,5	4040
	4	I	4	14,0	3535		8	O	9	68,0	4545
	5	I	4	16,2	3535	425	3	X	7	24,1	3535
236	6	I	4	19,0	3535		4	X	10	28,0	3535
	8	I	4	24,9	3535		5	X	10	34,0	3535
	3	I	4	12,0	3020		6	O	9	48,0	4040
250	4	I	4	17,2	3535	450	8	O	9	65,0	4545
	5	I	4	19,1	3535		10*	O	9	88,0	5050
	6	I	4	20,8	3535		3	X	7	26,0	3535
	8	I	4	25,5	3535		4	X	10	31,0	3535
265	2	I	4	9,8	3020	475	5	O	9	45,0	4040
	3	I	4	14,5	3020		6	O	9	58,0	4545
	4	I	4	20,7	3535		8	O	9	74,0	4545
	5	I	4	22,8	3535	500	3	X	7	28,6	3535
280	6	I	4	26,0	3535		4	X	10	33,5	3535
	8	I	4	29,7	3535		5	X	10	45,0	4040
	10*	I	4	34,0	4040		6	O	9	61,1	4545
280	3	I	8	21,2	3535	560	8	O	9	78,7	5050
	4	O	9	24,0	3535		10*	O	9	101,0	5050
	5	O	9	26,2	3535	630	3	X	7	40,0	3535
	6	O	9	29,0	3535		4	X	10	47,0	3535
300	8	O	9	33,3	3535		5	X	10	47,2	4040
	3	I	8	24,0	3535		6	O	9	62,8	4545
	4	O	9	29,0	3535	710	8	O	9	81,5	5050
	5	O	9	31,0	3535		3	X	7	30,9	3535
315	6	O	9	33,8	3535		4	X	10	39,0	3535
	8	O	9	37,5	3535		5	X	10	48,7	4040
	10*	O	9	45,0	4040		6	X	10	60,2	4545
335	3	O	5	21,0	3535		8	O	9	87,4	5050
	4	O	9	25,0	3535	500	10*	O	9	127,0	5050
	5	O	9	28,5	3535		3	X	7	36,0	3535
	6	O	9	29,0	3535		4	X	10	50,0	4040
335	8	I	4	46,5	4040	560	5	X	10	63,0	4545
	10*	O	9	53,5	4545		6	X	10	77,0	5050
315	3	O	5	21,6	3535		8	X	10	94,0	5050
	4	O	9	24,6	3535		10*	O	9	115,0	5050
	5	O	9	29,0	3535	630	3	X	7	48,5	4040
	6	O	9	31,4	3535		4	X	7	61,0	4545
335	8	I	4	50,0	4040		5	X	10	77,0	5050
	10*	O	9	58,0	4545		6	X	10	86,0	5050
335	3	O	5	22,5	3535		8	X	10	105,5	5050
	4	O	9	26,5	3535	710	10*	O	9	130,0	5050
	5	O	9	30,0	3535		3	X	7	62,5	4040
	6	O	9	35,0	3535		4	X	7	78,6	4545
335	8	O	9	58,0	4040		5	X	10	89,6	5050
	3	O	5	22,5	3535		6	X	10	99,4	5050
	4	O	9	26,5	3535		8	X	10	117,5	5050
	5	O	9	30,0	3535		10*	O	9	137,1	5050
	6	O	9	35,0	3535		3	X	7	62,5	4040
	8	O	9	58,0	4040		4	X	7	78,6	4545
	3	O	5	22,5	3535		5	X	10	89,6	5050
	4	O	9	26,5	3535		6	X	10	99,4	5050
	5	O	9	30,0	3535		8	X	10	117,5	5050
	6	O	9	35,0	3535		10*	O	9	137,1	5050
	8	O	9	58,0	4040		3	X	7	62,5	4040
	3	O	5	22,5	3535		4	X	7	78,6	4545
	4	O	9	26,5	3535		5	X	10	89,6	5050
	5	O	9	30,0	3535		6	X	10	99,4	5050
	6	O	9	35,0	3535		8	X	10	117,5	5050
	8	O	9	58,0	4040		10*	O	9	137,1	5050
▲ = alleen voor profiel 22											

Aantal groeven	2	3	4	5	6	8	10
Breedte b_2 (mm)	59,5	85	110,5	136	161,5	212,5	263,5
Klembus-Nr.	2517	3020	3535	4040	4545	5050	
Boring d_2 (mm) van ... tot ...	16-60	25-75	35-90	40-100	55-110	70-125	

I Volle schijf
O Bodem schijf
X Spaak schijf
Materiaal: EN-GJL 200 – DIN EN 1561
* Geen voorraad-artikel

Klembus-boringen d_2 zie blz. 102