

Profiel SPC/22 (Geen voorraad-artikel)

Steekcirkel d_d (mm)	Aantal groeven	Uitvoering	Gewicht (≈ kg)	Boring d_{max} (mm)	Naaf lengte l (mm)	Steekcirkel d_d (mm)	Aantal groeven	Uitvoering	Gewicht (≈ kg)	Boring d_{max} (mm)	Naaf lengte l (mm)	
180	1	O	4,2	40	54	335	2	X	14,0	55	74	
	2	O	7,2	50	64		3	X	18,3	55	90	
	3	O	10,4	55	90		4	X	22,4	60	95	
	4	O	10,5	55	95		5	X	28,3	65	100	
	5	O	18,0	60	100		6	X	34,4	75	115	
	6	O	23,6	65	115		355	2	X	15,2	60	74
200	1	O	4,8	40	54	3		X	19,2	70	90	
	2	O	7,8	50	64	4		X	25,8	70	95	
	3	O	8,8	55	90	5		X	32,0	75	100	
	4	O	11,2	60	95	6		X	36,2	75	115	
	5	O	15,4	65	100	400		3	X	20,6	70	90
	6	O	27,0	70	125		4	X	28,0	70	105	
225	1	X	5,5	48	54	450	5	X	32,0	75	100	
	2	X	7,8	52	64		2	X	21,1	70	80	
	3	X	10,6	52	90	3	X	26,3	75	90		
	4	X	13,1	55	95	4	X	31,1	75	105		
	5	X	16,7	60	100	5	X	42,2	80	110		
	6	X	35,0	60	115	6	X	48,5	80	120		
250	1	X	7,3	52	54	500	3	X	28,4	75	90	
	2	X	8,8	52	64		4	X	34,1	75	105	
	3	X	11,0	65	90		5	X	48,2	80	110	
	4	X	15,3	70	95		6	X	52,5	80	120	
	5	X	19,0	75	100		560	3	X	31,1	75	90
	6	X	23,7	60	115			4	X	39,0	75	105
280	1	X	8,7	52	54	630	5	X	54,1	80	110	
	2	X	10,9	55	64		6	X	61,5	85	120	
	3	X	15,6	70	90		3	X	38,5	80	90	
	4	X	17,5	75	95	4	X	48,1	80	105		
	5	X	20,5	75	100	5	X	62,2	85	110		
315	1	X	9,1	52	54		6	X	73,2	85	120	
	2	X	13,0	55	74							
	3	X	17,1	70	90							
	4	X	20,0	75	95							
	5	X	24,7	80	100							
	6	X	31,2	85	115							

Aantal groeven	1	2	3	4	5	6
Breedte b_2 (mm)	38	64	90	116	142	168

I Volle schijf
 O Bodem schijf
 X Spaak schijf
 Naaf lengte eenzijdig gelijk
 Materiaal: EN-GJL 200 – DIN EN 1561